# COSPOLICH

MODEL NUMBERS: MS2-2M-SNM MS3-2M-SNM

## MILK STORAGE REFRIGERATOR

From conception to production, the Milk Storage Refrigerator line was designed to be versatile, improve efficiency, and have ease of maintenance. The unit features a removable refrigeration cartridge and a robust design that will withstand rugged use.

## **APPLICATION**

The superior design of our products encompass quality, user comfort, as well as aesthetics. It is our interest that our Milk Storage Refrigerators not only look pleasing, but additionally provides function and service while complimenting the adjoining equipment in the service area.

# **CONSTRUCTION**

To compliment our design, we incorporate quality materials assembled by true craftsmen. Our use of heavy gauge type 304 stainless steel throughout inhibits corrosion and provides the best in sanitary conditions.

# **EQUIPMENT SPECIFICATIONS**

DIMENSIONAL DATA	MS2-2M-SNM	MS3-2M-SNM
Width Over all (in / mm)	27 in / 685.8 mm	38 in / 965.2 mm
Depth Overall (in / mm)	24 in / 609.6mm	24 in / 609.6mm
Height Overall (in / mm)	28.75 in / 222.25mm	28.75 in / 222.25mm
Weight (lbs / kg)	302 lbs / 136.98 kg	326 lbs /147.87 kg
ELECTRICAL DATA		
Voltage	115v	115v
Total Amperes (per well)	RLA: 5.3 amps Max Fuse: 15	RLA: 5.3 amps Max Fuse: 15
CLUDDING DATA		

#### SHIPPING DATA

Width-Crated (in / mm)	43in / 1092 mm	48 in / 850.9 mm
Depth-Crated (in / mm)	33.5 in / 850.9 mm	42.5 in / 1079.5 mm
Height-Crated (in / mm)	40 in / 1016 mm	63 in / 1600 mm
Weight-Crated (lbs / kg)	502 lbs / 227.7 kg	526 lbs / 238.59 kg




# MS2-2M-SNM

#### **FEATURES**

- Removable Refrigeration Cartridge Assembly
- Front Breathing Grill
- 4" Stainless Steel Foundation
- Electronic Controls





CONTACT FACTORY FOR YOUR SPECIFIC CAPACITY REQUIREMENTS